

PROSURF 170 SPEC SHEET

Non-Emulsifier



ProSurf 170 is a nonionic, non-emulsifying agent for use in all types of well stimulation. It is a versatile surfactant blend that provides strong water-wetting properties and interfacial tension reduction. ProSurf 170 is compatible with a wide range of acidizing and fracturing fluids and has been formulated to function with acid inhibitors without adversely affecting inhibitor corrosion rate. ProSurf 170 works effectively in 15% to 28% Hydrochloric Acid.

TYPICAL PHYSICAL PROPERTIES

- **Flash Point (°F/°C):** 92 / 33.3
- **Freeze Point (°F/°C):** 2 / -16.7
- **Charge:** Nonionic
- **Specific Gravity:** 0.957 - 1.017
- **Solubility:** Water, Acid, Brine, Oil

RECOMMENDED APPLICATION

- ProSurf 170 is used at a rate of 0.25 to 2 gal/1000 gal (gpt) acidizing or fracturing fluid. ProSurf 170 can be premixed or added on the fly. A compatibility test is advised before use.

PACKAGING

- ProSurf 170 is available in 55 gallon drums, 330 gallon totes or bulk transport. Other packaging options may be available upon request.

Contact our sales team to discuss elevating your performance at info@profrac.com or by phone at 254-PRO-FRAC.

