

# PROBREAK 670

■ Friction Reducer Breaker

## > PRODUCT DESCRIPTION

ProBreak 670 is an oxygenated compound that is used to break the friction reducer in slickwater systems. ProBreak 670 assists in preventing the formation of emulsions that can form if the polymer of the friction reducer is not broken.

## > PACKAGING

ProBreak 670 is available in 330 gallon totes. Other packaging options may be available upon request.

## > RECOMMENDED APPLICATION

ProBreak 670 is designed to be used in acidizing or frac treatment at 0.25-2.0 gal/1000 gal of spearhead fluid.

Recipes including ProBreak 670 are recommended to be verified appropriate for use on a case-by-case basis.

When using ProBreak 670 a compatibility test is recommended.

### Typical Physical Properties

Flash Point (°F/°C)	>200 / >93.9
Freeze Point (°F/°C)	14 / 10
Charge	Not Available
Specific Gravity	0.979 - 1.039
Solubility	Water, Acid, Brines

### Disclaimer

While the information and data contained herein are presented in good faith and believed to be reliable, nothing herein shall be deemed to constitute a warranty, express or implied, that the information or data is reliable, accurate, or complete or that the products described herein are merchantable or fit for a particular purpose or that said information, data, or products can be used without infringing the intellectual property rights of third parties. Individuals who receive the products or the information or data relating to the products described herein, must use their own judgment in determining fitness for a particular purpose. Unless otherwise stated, the information or data contained herein relates to the products when not used in conjunction with any other products or materials. ProFrac and its affiliates ("ProFrac") disclaim all express and implied warranties of merchantability, fitness for a particular purpose, and non-infringement. ProFrac shall not be liable for any loss or damage that may occur from the use of the products described herein, including the use of the products in conjunction with other products or materials, or reliance on the data or information described herein.