

# **PROCHEK 172**

#### Scale Inhibitor

# **PRODUCT DESCRIPTION**

ProChek 172 is a polymeric scale inhibitor designed to inhibit the formation of calcium sulfate, barium sulfate, and calcium carbonate scales.

ProChek 172 can be used in the spearhead of acid and frac treatments. ProChek 172 is designed to prevent damaging and production-robbing scale deposits in producing wells by batch, continuous, or squeeze treating. ProChek 172 is designed to be temperature stable to 480°F and can be effective at low doses. Performance testing is recommended at higher temperatures.

### **PACKAGING**

ProChek 172 is available in 330 gallon totes and bulk transport. Other packaging options may be available upon request.

### RECOMMENDED APPLICATION

ProChek 172 is used in fracturing fluids at 0.25-1.0 gal/1000 gal of frac fluid. ProChek 172 is used in the spearhead of an acid or frac treatment at 0.5-1.0 gal/1000 gal of spearhead fluid.

As previously noted, ProChek 172 may be able to be used in acid treatments; recipes including ProChek 172 are recommended to be verified sufficient for use on a case-by-case basis. When using ProChek 172 a compatibility test is recommended, especially at higher temperatures. ProChek 172 is compatible with non-ionic and anionic additives. Care should be taken when using with cationic materials.-

#### **Typical Physical Properties**

Flash Point (°F/°C)	> 200 / > 93.3
Freeze Point (°F/°C)	Not Available
Charge	Inorganic
Specific Gravity	1.25 - 1.30
Solubility	Water

#### Disclaimer

While the information and data contained herein are presented in good faith and believed to be reliable, nothing herein shall be deemed to constitute a warranty, express or implied, that the information or data is reliable, accurate, or complete or that the products described herein are merchantable or fit for a particular purpose or that said information, data, or products can be used without infringing the intellectual property rights of third parties. Individuals who receive the products or the information or data relating to the products described herein, must use their own judgment in determining fitness for a particular purpose. Unless otherwise stated, the information or data contained herein relates to the products when not used in conjunction with any other products or materials. ProFrac and its affiliates ("ProFrac") disclaim all express and implied warranties of merchantability, fitness for a particular purpose, and non-infringement. ProFrac shall not be liable for any loss or damage that may occur from the use of the products or materials, or reliance on the data or information described herein.

PROCHEK 172 IS DESIGNED TO AVOID THE USE OF DIESEL, NONYLPHENOL ETHOXYLATES, EGMBE, AND BTEX.