

PROCROSS 170

■ Instant Borate Cross-Linker

> **PRODUCT DESCRIPTION**

ProCross 170 is an instant, self-buffered cross-linker designed to be used in low guar polymer loading applications. ProCross 170 requires no pH control additives. ProCross 170 crosslinked gels are recommended in applications below 250°F.

> **PACKAGING**

ProCross 170 is available in 330 gallon totes and bulk transport. Other packaging options may be available upon request.

> **RECOMMENDED APPLICATION**

It is highly recommended that cross-link testing be performed prior to field application including the water and all other materials that will be incorporated in the job. Typical use rate ranges from 0.25 to 2.0 gal/Mgal in applications below 250°F BHT.

Typical Physical Properties

Flash Point (°F/°C)	> 200 / > 93.3
Freeze Point (°F/°C)	-30 / -34
Charge	Inorganic Salt
Specific Gravity	1.25 - 1.30
Solubility	Water

Disclaimer

While the information and data contained herein are presented in good faith and believed to be reliable, nothing herein shall be deemed to constitute a warranty, express or implied, that the information or data is reliable, accurate, or complete or that the products described herein are merchantable or fit for a particular purpose or that said information, data, or products can be used without infringing the intellectual property rights of third parties. Individuals who receive the products or the information or data relating to the products described herein, must use their own judgment in determining fitness for a particular purpose. Unless otherwise stated, the information or data contained herein relates to the products when not used in conjunction with any other products or materials. ProFrac and its affiliates ("ProFrac") disclaim all express and implied warranties of merchantability, fitness for a particular purpose, and non-infringement. ProFrac shall not be liable for any loss or damage that may occur from the use of the products described herein, including the use of the products in conjunction with other products or materials, or reliance on the data or information described herein.