

PROCROSS 370

■ Delayed Borate Cross-Linker

> PRODUCT DESCRIPTION

ProCross 370 is a delayed borate cross-linker for guar-based fluid systems. ProCross 370 can provide a cross-link delay of 1 to 5 minutes depending on the pH and the temperature of the system. The typical pH range for use is 10.5 to 12. ProCross 370 cross-linked gels can be used in temperatures up to and over 300°F.

> PACKAGING

ProCross 370 is available in 330 gallon totes and bulk transport. Other packaging options may be available upon request.

> RECOMMENDED APPLICATION

It is highly recommended that cross-link testing be performed prior to field application including the water and all other materials that will be incorporated in the job. Typical loadings range from 1.0 to 3.0 gal/Mgal for 20 to 40 lb. guar-based systems.

Typical Physical Properties

Flash Point (°F/°C)	> 200 / > 93
Freeze Point (°F/°C)	Not Available
Charge	Inorganic Salt
Specific Gravity	1.16 - 1.22
Solubility	Water Dispersible

Disclaimer

While the information and data contained herein are presented in good faith and believed to be reliable, nothing herein shall be deemed to constitute a warranty, express or implied, that the information or data is reliable, accurate, or complete or that the products described herein are merchantable or fit for a particular purpose or that said information, data, or products can be used without infringing the intellectual property rights of third parties. Individuals who receive the products or the information or data relating to the products described herein, must use their own judgment in determining fitness for a particular purpose. Unless otherwise stated, the information or data contained herein relates to the products when not used in conjunction with any other products or materials. ProFrac and its affiliates ("ProFrac") disclaim all express and implied warranties of merchantability, fitness for a particular purpose, and non-infringement. ProFrac shall not be liable for any loss or damage that may occur from the use of the products described herein, including the use of the products in conjunction with other products or materials, or reliance on the data or information described herein.