

PROSLICK 675

Friction Reducer

PRODUCT DESCRIPTION

ProSlick 675 is a dry, high-molecular weight anionic friction reducer that provides excellent drag reduction in freshwater as well as high TDS (Total Dissolved Solids) produced waters. ProSlick 675 can reduce friction at low dosages while still providing quick hydration and good viscosity building characteristics. ProFrac's line of dry friction reducers hydrate readily, with minimal shear required.

PACKAGING

ProSlick 675 is available in bulk transport and 50 pound sacks.

RECOMMENDED APPLICATION

ProSlick 675 should be mixed continuously on the fly using ProFrac approved dispensing equipment. Batch mixing is possible. Normal use rates will vary by application, with loadings of 1.25 to 8 pounds per 1000 gallons of fluid being common.

As with any fluid additive, compatibility testing is recommended prior to use. Please note that ProSlick 675 is anionic and compatibility testing should be conducted, particularly when cationic additives are used.

ProSlick 675 may be cleaned from equipment using d-Limonene OF, LF-15 or MFS-Green. Depending upon the level of clean-up needed, these clean-up materials may be effectively used for up to three separate rinses.

Typical Physical Properties

Flash Point (°F/°C)	Not Available
Freeze Point (°F/°C)	Not Available
Charge	Anionic
Specific Gravity	0.80 - 1.50
Solubility	Water

Disclaimer

While the information and data contained herein are presented in good faith and believed to be reliable, nothing herein shall be deemed to constitute a warranty, express or implied, that the information or data is reliable, accurate, or complete or that the products described herein are merchantable or fit for a particular purpose or that sid information, data, or products can be used without infringing the intellectual property rights of third parties. Individuals who receive the products or the information or data contained herein must use their own judgment in determining fitness for a particular purpose. Unless otherwise stated, the information or data contained herein relates to the products when not used in conjunction with any other products or materials. ProFrac and its affiliates ("ProFrac") disclaim all express and implied warranties of merchantability, fitness for a particular purpose, and non-infringement. ProFrac shall not be liable for any loss or damage that may occur from the use of the products described herein, including the use of the products in conjunction with other products or materials, or reliance on the data or information described herein.